

Stainless Steel 304 3-way Ball Valve Flanged End JIS 10K



Three-way ball valves are used to switch over, mix and divide the flow of corrosive or noncorrosive liquid, gas or powdery mediums. Upon opening and closing, the smooth flow channel effects less pressure loss, making operation quite labor-saving and maintenance fairly easy.

Available in T-port and L-port



Features :

Test Pressure :
Shell Test : 3.0 Mpa
Seat Test : 2.2 Mpa
Air Seal Test : 0.2 Mpa
Temperature : -40 ~ 180 deg C

Dimension

mm

DN	L	L1	D	D1	D2	d	b	Z-d	
15	1/2"	150	75	95	70	52	15	12	4-15
20	3/4"	160	80	100	75	58	20	14	4-15
25	1"	180	90	125	90	70	25	14	4-19
32	1 1/4"	200	100	135	100	80	32	16	4-19
40	1 1/2"	220	110	140	105	85	40	16	4-19
50	2"	240	120	155	120	100	50	16	4-19
65	2 1/2"	240	130	175	140	120	65	18	4-19
80	3"	280	140	185	150	130	80	18	8-19
100	4"	320	160	210	175	155	100	18	8-19
125	5"	380	190	250	210	185	125	20	8-23
150	6"	440	220	280	240	215	150	22	8-23
200	8"	550	275	330	290	265	200	22	12-23



Material

No.	Part Name	Material
1	Body	SS304
2	Seat	PTFE
3	Ball	SS304
4	Housing	SS304
5	Bolt	SS304
6	Gasket	PTFE
7	Flange End	SS304
8	Stem	SS304
9	Gland Washer	SS304
10	Stem Packing	PTFE
11	Gland	SS304
12	Blank End	SS304

The contents of this literature are for informative purposes only. Arita is not responsible for suitability or compatibility of these Products in relation to system requirement. For specific requirements, consult Arita or its distributors. Arita reserves the right to change or modify product design without prior notice.