

# YBT-4 Bucket Trap

As an optimal trap for drain discharge for steam pipelines and headers, it has a simple structure that ensures easy maintenance.



## ■ Features

- Simple structure & extremely strong parts : durability and effective operations are guaranteed.
- No air binding : inverted structure of the bucket.
- No need to attach a separate strainer : bucket trap with built-in screen.
- Easy repair : simply remove the cover.

## ■ Specifications

Type		YBT-4
Applicable pressure		Maximum 17 kgf/cm²g
Fluid temperature		220° C below
End connection		KS PT SCREW
Materials	Body	GCD450
	Disc, seat	STS
Hydraulic test pressure		25 kgf/cm²g

## ■ Maximum applicable differential pressure

Size	Applicable differential pressure (Psi)
15(1/2")	80 / 125 / 230
20(3/4")	
25(1")	

## ■ Dimensions


(mm)

Size	L	H1	H2	D	Weight(kg)
15(1/2")	127	78	65	1/2"	2.7
20(3/4")	127	78	65	3/4"	2.7
25(1")	127	100	65	1"	3.0

## ■ Cautions during installation

- After installing a bypass line and before operating the trap, blow out and remove foreign substances from inside the pipeline.
- The trap should be installed horizontally.
- The location of trap installation in the pipeline should be the lowest point of the facility or the end of the pipeline. If the outlet side is vertically standing, the height of the trap should be within the allowed back pressure range.

## ■ Dimensional drawing



## ■ Flow curve

